



PRODUCT DATA SHEET

Product view




Product information

| | |
|---------------|----------------------|
| Article group | Plug Adaptor |
| Item number | CRA11020 |
| EAN / GTIN | 4260182340202 |
| Designation | Plug Adaptor CSA 100 |

Product description

Internal adapter for connecting two piping systems with the same pipe dimensions (DN) as well as for the same or different materials and surface structures; noise-reducing sealing lips; recommended for vertical installation for black water; suitable for horizontal or vertical installation for grey water; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration



Dimensioning

| | |
|-----------------------------|----------------|
| A Size range | 100-116 mm |
| B Clamping range | 100-105 mm |
| L Length / E Plug depth | 115 mm / 45 mm |

Specification

| | |
|-----------------------------------|--|
| Pressure density | 0,5 bar |
| Vacuum pressure density | -0,3 bar |
| High-pressure flushing resistance | 120 bar |
| Socket wrench insert | SW 8 mm |
| Tightening torque | 6,0 Nm |
| Weight | 0.311 kg |
| Material | TPE, Stainless steel (AISI 304), PVC (white) |

CE marking

| | |
|--------------|----------|
| according to | EN 681-2 |
|--------------|----------|

Resistances

| | |
|-----------------------|--------|
| Heat resistant | 140 °C |
| Cold resistant | -60 °C |
| UV resistant | ✓ |
| Suitable for soil | ✓ |
| Flush-mounting suited | ✓ |

