



PRODUCT DATA SHEET

Product view





Article group	Standard Coupling Type 2B XL
Item number	CRA16902
EAN / GTIN	4260431853088
Designation	Standard Coupling CSC XL 310

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; wider support area with 300mm; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration

Dimensioning







	opecinication	
	Pressure density	2,5 bar
	Vacuum pressure density	-0,3 bar
	High-pressure flushing resistance	120 bar
	Socket wrench insert	SW 8 mm
	Tightening torque	10 Nm
	Weight	5 kg
	Material	EPDM, Stainless steel (AISI 304)
	OF	

CE marking according to EN 681-1, EN 16397 Resistances Heat resistant 120 °C Cold resistant -40 °C UV resistant ✓	Material	EPDM, Stainless steel (AISI 304)
Resistances Heat resistant 120 °C Cold resistant -40 °C	CE marking	
Heat resistant 120 °C Cold resistant -40 °C	according to	EN 681-1, EN 16397
Cold resistant -40 °C	Resistances	
	Heat resistant	120 °C
UV resistant 🗸	Cold resistant	-40 °C
	UV resistant	•

Suitable for soil

Flush-mounting suited