CRASSUS

be smart. be a Problemlöser.

Product datasheet as a PDF file

PRODUCT DATA SHEET

Product view

Product information

Designation	Adaptor Coupling CAC 1221
Item number	**CRA12040**

Product description

External adapter for connecting two piping systems with different external diameters as well as different materials or surface structures; for reducing various pipe dimensions; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration





Dimensioning

A | Size range	110-122 mm
B | Clamping range	80-95 mm
L | Length	100 mm

Specification

Pressure-tightness	0.6 bar / 8.7 PSI
Vacuum pressure tightness	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	6,0 Nm
Angular deviation (max.)	5,0°
Insertion depth (min.)	25 mm
Product-related standard	EN 681-1, EN 16397, EN 295-4
Weight	0.46 kg
Material	EPDM, Stainless steel (AISI 304)

Resistances

Temperature resistance	-40 / 120 °C
UV resistant	✔
Suitable for soil	✔
Flush-mounting suited	✔

Crassus GmbH & Co. KG
Josef-Orlopp-Straße 37
10365 Berlin, Germany
Local court Berlin
HRA 50944 B

Personally liable partner
Crassus Verwaltungs GmbH
Management Lars Baier
Local court Berlin
HRB 167557 B

Do you have any questions? USt-IdNr. DE300242912
Tel +49 30 3474 765-0
Fax +49 30 3474 765-20
Email info@crassus.de
Web www.crassus.de