CRASSUS

be smart. be a Problemlöser.

Product datasheet as a PDF file

PRODUCT DATA SHEET

Product view

Technical illustration





Product information

Designation	Adaptor Coupling CAC 2655
Item number	CRA17190

Product description

External adapter for connecting two piping systems with different external diameters as well as different materials or surface structures; for reducing various pipe dimensions; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Dimensioning

A | Size range	240-265 mm
B | Clamping range	170-192 mm
L | Length	150 mm

Specification

Pressure-tightness	0.6 bar / 8.7 PSI
Vacuum pressure tightness	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	6,0 Nm
Angular deviation (max.)	3,0°
Insertion depth (min.)	45 mm
Product-related standard	EN 681-1, EN 16397, EN 295-4
Weight	1.64 kg
Material	EPDM, Stainless steel (AISI 304)

Resistances

Temperature resistance	-40 / 120 °C
UV resistant	✔
Suitable for soil	✔
Flush-mounting suited	✔

Crassus GmbH & Co. KG
Josef-Orlopp-Straße 37
10365 Berlin, Germany
Local court Berlin
HRA 50944 B

Personally liable partner
Crassus Verwaltungs GmbH
Management Lars Baier
Local court Berlin
HRB 167557 B

Do you have any questions? USt-IdNr. DE300242912
Tel +49 30 3474 765-0
Fax +49 30 3474 765-20
Email info@crassus.de
Web www.crassus.de