



PRODUCT DATA SHEET

Product view





Article group	Standard Coupling Type 2B FKM
Item number	CRA16110FKM
EAN / GTIN	4260431851657
Designation	Standard Coupling CSC 265 FKM

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration

Dimensioning



A Size range	240-265 mm
L Length	150 mm

2,5 bar

Specification Pressure density

Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm

Tightening torque	10.0 Nm
Weight	1.6 kg

Material	FKM, Stainless steel (AISI 304)

CE marking

according to	ISO 1629, ASTM D 1418

Resistances

Do you have any questions? USt-IdNr. DE300242912 Tel $+49\,30\,3474\,765-0$ Fax $+49\,30\,3474\,765-20$ Email info@crassus.de Web www.crassus.de

Heat resistant	200 °C
Cold resistant	-25 °C
UV resistant	✓
Suitable for soil	✓
Flush-mounting suited	✓



Josef-Orlopp-Straße 37 10365 Berlin, Germany