



# **PRODUCT DATA SHEET**

### **Product view**

### **Product information**



| Article group | Standard Coupling Type 2B XL |
|---------------|------------------------------|
| Item number   | CRA16924                     |
| EAN / GTIN    | 4260431853309                |
| Designation   | Standard Coupling CSC XL 620 |

# **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; wider support area with 300mm; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

#### **Technical illustration**

## **Dimensioning**

**CE** marking







| Specification                     |                                  |
|-----------------------------------|----------------------------------|
| Pressure density                  | 2,5 bar                          |
| Vacuum pressure density           | -0,3 bar                         |
| High-pressure flushing resistance | 120 bar                          |
| Socket wrench insert              | SW 8 mm                          |
| Tightening torque                 | 13.0 Nm                          |
| Weight                            | 10.9 kg                          |
| Material                          | EPDM, Stainless steel (AISI 304) |
|                                   |                                  |

| according to | EN 681-1, EN 16397 |
|--------------|--------------------|
| Resistances  |                    |
|              |                    |

| Heat resistant        | 120 °C |
|-----------------------|--------|
| Cold resistant        | -40 °C |
| UV resistant          | •      |
| Suitable for soil     | •      |
| Flush-mounting suited | •      |