



PRODUCT DATA SHEET

Product view

Product information



Article group	Standard Coupling Type 2B
Item number	CRA16235
EAN / GTIN	4260182341100
Designation	Standard Coupling CSC 525

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration

Dimensioning



Specification	
L Length	190 mm
A Size range	495-525 mm



Specification	DECINCATION	
Pressure density	2,5 bar	
Vacuum pressure density	-0,3 bar	
High-pressure flushing resistance	120 bar	
Socket wrench insert	SW 8 mm	
Tightening torque	13.0 Nm	
Weight	5.2 kg	
Material	EPDM, Stainless steel (AISI 304)	

according to	
Resistances	

Do you have any questions? USt-IdNr. DE300242912 Tel $+49\,30\,3474\,765-0$ Fax $+49\,30\,3474\,765-20$ Email info@crassus.de Web www.crassus.de

CE marking

	Heat resistant	120 °C
	Cold resistant	-40 °C
	UV resistant	•
	Suitable for soil	•
	Flush-mounting suited	•

EN 681-1, EN 16397

Crassus GmbH & Co. KG

Josef-Orlopp-Straße 37 10365 Berlin, Germany