

be smart. be a Problemlöser.




# **PRODUCT DATA SHEET**

#### **Product view**



## **Technical illustration**



#### **Product information**

| Article group | Standard Coupling Type 2B |
|---------------|---------------------------|
| Item number   | CRA16645                  |
| EAN / GTIN    | 4260182341452             |
| Designation   | Standard Coupling CSC 450 |
|               |                           |

## **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

### Dimensioning

| A   Size range                    | 425-450 mm                       |
|-----------------------------------|----------------------------------|
| L   Length                        | 190 mm                           |
| Specification                     |                                  |
| Pressure density                  | 2,5 bar                          |
| Vacuum pressure density           | -0,3 bar                         |
| High-pressure flushing resistance | 120 bar                          |
| Socket wrench insert              | SW 8 mm                          |
| Tightening torque                 | 13.0 Nm                          |
| Weight                            | 4.4 kg                           |
| Material                          | EPDM, Stainless steel (AISI 304) |
| CE marking                        |                                  |
| according to                      | EN 681-1, EN 16397               |
| Resistances                       |                                  |
| Heat resistant                    | 120 °C                           |
| Cold resistant                    | -40 °C                           |
| UV resistant                      | 1                                |
| Suitable for soil                 | 1                                |
| Flush-mounting suited             | 1                                |
|                                   |                                  |



Crassus GmbH & Co. KG Josef-Orlopp-Straße 37 10365 Berlin, Germany Local court Berlin HRA 50944 B

Co. KG Personally liable partner 37 Crassus Verwaltungs GmbH any Management Lars Baier Local court Berlin HRB 167557 B

**Do you have any questions? USt-IdNr. DE300242912** Tel +49 30 3474 765-0 Fax +49 30 3474 765-20 Email info@crassus.de Web www.crassus.de