



PRODUCT DATA SHEET

Product view



Product information

Article group	Standard Coupling Type 2B
Item number	CRA16814
EAN / GTIN	4260431852470
Designation	Standard Coupling CSC 1130

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration





Dimensioning

Do you have any questions? USt-IdNr. DE300242912 Tel $+49\,30\,3474\,765-0$ Fax $+49\,30\,3474\,765-20$ Email info@crassus.de Web www.crassus.de

A Size range	1115-1130 mm
L Length	190 mm
Specification	
Pressure density	1,0 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 13 mm
Tightening torque	20 Nm
Weight	12.6 kg
Material	EPDM, Stainless steel (AISI 304)
CE marking	
according to	EN 681-1, EN 16397
Resistances	
Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	,
OV TESISLATIC	✓
Suitable for soil	•

