



PRODUCT DATA SHEET

Product view





| Article group | Floor Drain Sealing Flange |
|---------------|--------------------------------|
| Item number | CRA22803 |
| EAN / GTIN | 4260431850209 |
| Designation | Floor Drain PVC Sealing Flange |


Product description

For installation outdoors in areas without traffic; for the drainage of greywater; flow rate: 1.67 l/s; with pressure-waterproof, circumferential Crassus 3-ridge seal; oil- and bitumen-resistant foil flange (d = approx. 50 cm); screw-on stainless steel grate Class K3 (loadable up to max. 300 kg) 15x15 cm; frost-proof odor trap, sludge trap sieve, and construction-time protection cover; construction height: drain approximately 110 mm, mounting frame continuously adjustable and rotatable from 30-70 mm; connection: PVC pipes DN 110 vertically; according to DIN 1253; according to DIN 18533 W1-E and W2.1-E

Technical illustration

Dimensioning

Do you have any questions? USt-IdNr. DE300242912 Tel $+49\,30\,3474\,765-0$ Fax $+49\,30\,3474\,765-20$ Email info@crassus.de Web www.crassus.de



| A Plastic grate | 150x150 mm |
|--------------------------------|--|
| B Connection pipe ø | DN 110 mm |
| Specification | |
| Pressure density | 2.5 bar |
| Weight | 1.1 kg |
| Material | KG pipe (PVC), Stainless steel (AISI 304), |
| | EPDIM |
| Testing / Approval | MPA |
| Testing / Approval Resistances | |
| | |
| Resistances | MPA |