



PRODUCT DATA SHEET

Product view





Article group	Standard Coupling Type 2B FKM
Item number	CRA14037FKM
EAN / GTIN	4260431851619
Designation	Standard Coupling CSC 115 FKM

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration

Dimensioning





	Ultres .	****
	Same.	
0	Mining	5 J
60	Mining	= M
	Stand	

CE marking	
Material	FKM, Stainless steel (AISI 304)
Weight	0.7 kg
Tightening torque	6,0 Nm
Socket wrench insert	SW 8 mm
High-pressure flushing resistance	120 bar
Vacuum pressure density	-0,3 bar
Pressure density	2,5 bar
Specification	

according to	ISO 1629, ASTM D 1418
Resistances	
Heat resistant	200 °C

Heat resistant	200 °C
Cold resistant	-25 °C
UV resistant	•
Suitable for soil	•
Flush-mounting suited	1