



PRODUCT DATA SHEET

Product view




Product information

Article group	Floor Drain Sealing Flange
Item number	CRA22803
EAN / GTIN	4260431850209
Designation	Floor Drain PVC Sealing Flange

Product description

For installation outdoors in areas without traffic; for the drainage of greywater; flow rate: 1.67 l/s; with pressure-waterproof, circumferential Crassus 3-ridge seal; oil- and bitumen-resistant foil flange (d = approx. 50 cm); screw-on stainless steel grate Class K3 (loadable up to max. 300 kg) 15x15 cm; frost-proof odor trap, sludge trap sieve, and construction-time protection cover; construction height: drain approximately 110 mm, mounting frame continuously adjustable and rotatable from 30-70 mm; connection: PVC pipes DN 110 vertically; according to DIN 1253; according to DIN 18533 W1-E and W2.1-E

Technical illustration



Dimensioning

A Plastic grate	150x150 mm
B Connection pipe ø	DN 110 mm

Specification

Pressure density	2.5 bar
Weight	1.1 kg
Material	KG pipe (PVC), Stainless steel (AISI 304), EPDM

Testing / Approval	MPA
---------------------------	-----

Resistances

UV resistant	✓
Suitable for soil	✓
Flush-mounting suited	✓

