



PRODUCT DATA SHEET

Product view





Article group	Standard Coupling Type 2B XL
Item number	CRA16902
EAN / GTIN	4260431853088
Designation	Standard Coupling CSC XL 310

Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; wider support area with 300mm; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

Technical illustration

Dimensioning

Do you have any questions? USt-IdNr. DE300242912 Tel $+49\,30\,3474\,765-0$ Fax $+49\,30\,3474\,765-20$ Email info@crassus.de Web www.crassus.de







Specification	
Pressure density	2,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	10 Nm
Weight	5 kg
Material	EPDM, Stainless steel (AISI 304)
CE marking	

CE marking		
according to	EN 681-1, EN 16397	
Resistances		
Heat resistant	120.90	

Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	✓
Suitable for soil	✓
Flush-mounting suited	•