

be smart. be a Problemlöser.



## **PRODUCT DATA SHEET**

Article group

Item number

EAN / GTIN

Designation

**Product information** 


**Product description** 

weather-resistant material.

## **Product view**



## **Technical illustration**



## Dimensioning

<b>J</b>	
A   Size range	100-116 mm
B   Clamping range	100-105 mm
L   Length / E   Plug depth	115 mm / 45 mm
Specification	
Pressure density	0,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	6,0 Nm
Weight	0.311 kg
Material	TPE, Stainless steel (AISI 304), PVC (white)
CE marking	
according to	EN 681-2
Resistances	
Heat resistant	140 °C
Cold resistant	-60 °C
UV resistant	•
Suitable for soil	•
Flush-mounting suited	٠

Plug Adaptor

CRA11020

Internal adapter for connecting two piping systems with the same pipe dimensions (DN) as well as for the same or different materials and surface

structures; noise-reducing sealing lips; recommended for vertical installation for black water; suitable for horizontal or vertical installation for grey water; suitable for use in plaster, concrete, and soil; UV and

4260182340202

Plug Adaptor CSA 100



Crassus GmbH & Co. KG Josef-Orlopp-Straße 37 10365 Berlin, Germany Local court Berlin HRA 50944 B

o. KG Personally liable partner Crassus Verwaltungs GmbH Iny Management Lars Baier Local court Berlin HRB 167557 B

 Do you have any questions? USt-IdNr. DE300242912

 H
 Tel +49 30 3474 765-0

 Fax +49 30 3474 765-20
 Email info@crassus.de

 Web www.crassus.de
 Web www.crassus.de

Query date 09.05.2024, Time 22:56 (CET) tr-en