



## **PRODUCT DATA SHEET**

#### **Product view**





Article group	Standard Coupling Type 2B
Item number	CRA14037
EAN / GTIN	4260182340370
Designation	Standard Coupling CSC 116

#### **Product description**

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

#### **Technical illustration**

#### **Dimensioning**

	-	120	-
1			
- 116		1	
100			
,		Ш	Щ
	್	<del>7 0</del>	- ಅ

A   Size range	100-116 mm
L   Length	120 mm

### **Specification**

Pressure density	2,5 bar
Vacuum pressure density	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	6,0 Nm
Weight	0.704 kg
Material	EPDM, Stainless steel (AISI 304)

# **CE** marking

according to	EN 681-1, EN 16397
Resistances	

Do you have any questions? USt-IdNr. DE300242912 Tel  $+49\,30\,3474\,765-0$  Fax  $+49\,30\,3474\,765-20$  Email info@crassus.de Web www.crassus.de

Heat resistant	120 °C
Cold resistant	-40 °C
UV resistant	/
Suitable for soil	/
Flush-mounting suited	<b>✓</b>



Crassus GmbH & Co. KG

Josef-Orlopp-Straße 37 10365 Berlin, Germany