



## PRODUCT DATA SHEET

### Product view




### Product information

Designation	Standard Coupling CSC 290
Item number	<b>CRA16222</b>

### Product description

External adapter for connecting two piping systems with the same pipe dimensions (DN), as well as for the same or different materials and surface structures; suitable for high shear force loads; differences in external diameter of more than 10 mm should be compensated with Crassus compensating rings; noise-reducing sealing lips; suitable for horizontal or vertical installation; suitable for use in plaster, concrete, and soil; UV and weather-resistant material.

### Technical illustration



### Dimensioning

A   Size range	265-290 mm
L   Length	150 mm

### Specification

Pressure-tightness	2.5 bar / 36.3 PSI
Vacuum pressure tightness	-0,3 bar
High-pressure flushing resistance	120 bar
Socket wrench insert	SW 8 mm
Tightening torque	10.0 Nm
Angular deviation (max.)	3,0°
Insertion depth (min.)	60 mm
Product-related standard	EN 681-1, EN 16397, EN 295-4, EN 10088-2
Weight	1.7 kg
Material	EPDM, Stainless steel (AISI 304)

### Resistances

Temperature resistance	-40 / 120 °C
UV resistant	✓
Suitable for soil	✓
Flush-mounting suited	✓

